

Suitable for Heat Pumps, Heat Recovery Units, Process and Industrial Chillers, Air Handling Units, Pumping and more

www.se.com

Modicon TM1730

The powerful PLC for compact machines



Low-GWP gas ready

Conform to EN/IEC 60335-2-40 related to A3 refrigerants, such as R290 Suitable for A2L

Small dimensions

4-DIN module in three versions

Green Premium product

Sustainable performance, by Design Compliance with environmental regulations

1MB to support simple and complex programs

Less is more

Insulation everywhere simplifying machine wiring diagram and reducing the number of components

Adaptive

One unit for super compact machines; for bigger ones, just add I/O expansions



Flexible & Configurable

22 IOs to adapt to different machines

Inputs: NTC, PT1000, 0...5V, 0...10V, 4...20mA,voltage free, Pulse counter

Outputs: Relay, SSR, PWM, 0...10V, 4...20mA

Integrated EEVD

Integrated Unipolar Electronic Expansion valve driver

Ready-to-use assets

simplifying programming IEC61131 - Many templates, libraries, function blocks available

Multiple connection capabilities

to the other devices inside the machine Modbus RTU client and server, CANopen, USB-C, Remote display bus

IoT on deck

Straightforward connection to the Secure Interface: cybersecure IoT module

Codes	Description
TM173ODM22R	TM173 optimized, display, 22 IOs, 24 Vac/dc, 2 x RS485
TM173ODM22S	TM173 optimized, display, 22 IOs, 24 Vac/dc, 2 x RS485, 2 x SSR
TM173OBM22R	TM173 optimized, 22 IOs, 24 Vac/dc, 2 x RS485

Digitization



Learn more about our products at www.se.com

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Design: Schneider Electric Photos: Schneider Electric

Schneider Electric Industries SAS Head Office 35, rue Joseph Monier - CS 30323 F-92500 Rueil-Malmaison Cedex France